

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently Amended)

A method for setting an operating mode of a processor by writing a control flag included in a processor control register of ~~a processor~~ the processor by a guest virtual machine, the method comprising:

determining whether the control flag is owned by the guest virtual machine;

writing the control flag to the processor control register if the control flag is owned by the guest virtual machine; and

writing the control flag to a shadow location in a guest virtual machine context in a memory coupled to the processor if the control flag is not owned by the guest virtual machine.

2. (Original)

The method of claim 1, wherein determining whether the control flag is owned by the guest virtual machine further comprises testing a first flag in a mask word.

3. (Original)

The method of claim 1, further comprising:

determining whether the control flag is maintained in the shadow location;

writing the control flag to the shadow location if the control flag is not owned by the guest virtual machine and is maintained in the shadow location; and

exiting to a virtual machine monitor if the control flag is not owned by the guest virtual machine and is not maintained in the shadow location.

4. (Original)

The method of claim 3, wherein determining whether the control flag is maintained in a shadow location is performed only if the control flag is not owned by the guest virtual machine.

5. (Previously Presented)

The method of claim 3, wherein determining whether the control flag is maintained in a shadow location further comprises testing a flag.

6. (Currently Amended)

A method for determining an operating mode of a processor by reading a control flag included in a processor control register of ~~a processor~~ the processor by a guest virtual machine hosted by the processor, the method comprising:

determining whether the control flag is maintained in a shadow location in a guest virtual machine context in a memory coupled to the processor;

reading the control flag from the shadow location if the control flag is maintained in the shadow location; and

reading the control flag from a processor control register of the processor if the control flag is not maintained in the shadow location.

7. (Original)

The method of claim 6, wherein determining whether the control flag is maintained in a shadow location further comprises determining whether the control flag is owned by the guest virtual machine.

8. (Original)

The method of claim 6, wherein determining whether the control flag is maintained in a shadow location further comprises testing a flag in a mask word.

9. (Currently Amended)

A processor comprising:

a processor control register ~~to include that includes a control flag; flag that determines an~~
operating mode of the processor;

a pointer to a guest virtual machine ~~context; context in a portion of a random access~~
memory (RAM) coupled to the processor;

~~a first mask word in the guest virtual machine context, the first mask word to include a~~
~~first flag to indicate whether the control flag is owned by a guest virtual machine~~
~~associated with the guest virtual machine context;~~

~~a shadow location in the guest virtual machine context;~~

an execution control unit

to test a first flag in the guest virtual machine context, the first flag to indicate whether the control flag is owned by a guest virtual machine associated with the guest virtual machine context, and
to cause a write of the control flag by the guest virtual machine to be directed to the processor control register if the control flag is owned by the guest virtual machine and to be redirected to ~~the shadow~~ a shadow location in the guest virtual machine context
if the control flag is not owned by the guest virtual machine.

10. (Original)

The processor of claim 9, further comprising:

a second mask word in the guest virtual machine context, the second mask word to include a second flag to indicate whether the control flag is maintained in the shadow location;

wherein the execution control unit is further

to cause a write of the control flag by the guest virtual machine to be redirected to the shadow location if the control flag is not owned by the guest virtual machine and is maintained in the shadow location, and
to cause an exit to a virtual machine monitor if the control flag is not owned by the guest virtual machine and is not maintained in the shadow location.

11. (Original)

The processor of claim 10, wherein the execution control unit is responsive to the second flag only if the first flag indicates that the control flag is not owned by the guest virtual machine.

12. (Currently Amended)

A processor comprising:

a processor control register;

a control flag included in the processor control ~~register; register, the control flag to~~
determine an operating mode of the processor;

means for detecting the writing of the control flag by a guest virtual machine;

means for determining whether the control flag is owned by the guest virtual machine;

means for writing the control flag to the processor control register if the control flag is owned by the guest virtual machine; and

means for writing the control flag to a shadow location in a guest virtual machine context in a memory coupled to the processor if the control flag is not owned by the guest virtual machine.

13. (Original)

The processor of claim 12, wherein means for determining whether the control flag is owned by the guest virtual machine further comprises means for testing a first flag in a mask word.

14. (Original)

The processor of claim 12, further comprising:

means for determining whether the control flag is maintained in the shadow location;

means for writing the control flag to the shadow location if the control flag is not owned by the guest virtual machine and is maintained in the shadow location; and

means for exiting to a virtual machine monitor if the control flag is not owned by the guest virtual machine and is not maintained in the shadow location.

15. (Original)

The processor of claim 14, wherein means for determining whether the control flag is maintained in a shadow location is operative only if the control flag is not owned by the guest virtual machine.

16. (Previously Presented)

The processor of claim 14, wherein means for determining whether the control flag is at or maintained in a shadow location further comprises means for testing a flag.

17. (Currently Amended)

An article of manufacture comprising:

a machine-accessible medium including data that, when accessed by a processor, cause the processor to perform operations comprising,

determining whether a control flag included in a processor control register of the processor is owned by a guest virtual ~~machine~~; machine, the control flag to determine an operating mode of the processor;

writing the control flag to a processor control register if the control flag is owned by the guest virtual machine; and

writing the control flag to a shadow location in a guest virtual machine context in a memory coupled to the processor if the control flag is not owned by the guest virtual machine.

18. (Original)

The article of manufacture of claim 17 wherein the machine-accessible medium further includes data that cause the processor to perform operations comprising testing a first flag in a mask word to determine whether the control flag is owned by the guest virtual machine.

19. (Original)

The article of manufacture of claim 17 wherein the machine-accessible medium further includes data that cause the processor to perform operations comprising:

determining whether the control flag is maintained in the shadow location;

writing the control flag to the shadow location if the control flag is not owned by the guest virtual machine and is maintained in the shadow location; and

exiting to a virtual machine monitor if the control flag is not owned by the guest virtual machine and is not maintained in the shadow location.

20. (Original)

The article of manufacture of claim 19 wherein determining whether the control flag is maintained in a shadow location is performed only if the control flag is not owned by the guest virtual machine.

21. (Previously Presented)

The article of manufacture of claim 19 wherein the machine-accessible medium further includes data that cause the processor to perform operations comprising testing a flag to determine whether the control flag is maintained in a shadow location.

22. (Currently Amended)

A system comprising:

a processor;

~~a processor control register including a control flag;~~

a memory coupled to the processor, the memory selected from one of an SDRAM memory and an RDRAM memory, the memory to maintain a guest virtual machine context;

~~a pointer to the guest virtual machine context;~~

a processor control register that determines an operating mode of the processor, the processor control register including a control flag, the processor control register being outside the guest virtual machine context;

a first mask word in the guest virtual machine context, the first mask word to include a first flag in to indicate whether the control flag is owned by a guest virtual machine associated with the guest virtual machine context;

a shadow location in the guest virtual machine context;

an execution control unit to test the first flag and to cause a write of the control flag by the guest virtual machine to be directed to the processor control register if the control flag is owned by the guest virtual machine and to be redirected to the shadow location if the control flag is not owned by the guest virtual machine.

23. (Original)

The system of claim 22, further comprising:

a second mask word in the guest virtual machine context, the second mask word to include a second flag in to indicate whether the control flag is maintained in the shadow location;

wherein the execution control unit is further

to cause a write of the control flag by the guest virtual machine to be redirected to the shadow location if the control flag is not owned by the guest virtual machine and is maintained in the shadow location, and
to cause an exit to a virtual machine monitor if the control flag is not owned by the guest virtual machine and is not maintained in the shadow location.

24. (Original)

The system of claim 23, wherein the execution control unit is responsive to the second flag only if the first flag indicates that the control flag is not owned by the guest virtual machine.